

SPP-R400

4 inch Mobile Printer

Mobile POS
/ Retail

Deliveries

Customer
Service Center

Ticketing

Robust and Powerful



Enhanced Convenience

- Compatible with smart devices including iPhone, iPad, and Android
- Place entire device on cradle for an effortless charge
- Versatile connectivity (WLAN, Bluetooth, etc.)
- One touch cover open and simple drop-in paper loading



Improved Printing Performance

- Linerless label printing (optional)
- Easily switch from receipt to label printing
- Low-temp (-15°C) printing with an integrated temperature sensor
- Faster printing speeds of up to 80 mm/sec (Receipt)
- Enhanced printing of fonts, graphics, and barcode symbologies



Mobile Field-Work Optimization

- Handy yet robust design
- Water and dust resistant (IP54 with protective case)
- Long-lasting battery life
- Optional Integrated Card Reader (MSR)

BIXOLON®
a Better Solution for your Business™

SPP-R400

4 inch Mobile Printer

Specifications

Printer Specifications

Print Method
Direct Thermal

Print Speed
Up to 80 mm/sec (Receipt)
Up to 50 mm/sec (Linerless)
12.5% pattern

Print Resolution
203 dpi

Print Width
Up to 104 mm

Sensor
Paper End: Reflective sensor
Paper Cover Open: Mechanical switch

Media Characteristics

Media Type
Receipt and Label, Linerless (optional)

Media Width
112 mm
105 mm (optional)

Media Roll Diameter
Up to 57 mm

Media Thickness
0.07 ± 0.003 mm

Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)
147.0 x 171.4 x 66.7 mm
(5.79 x 6.75 x 2.63 inch)

Weight
Including battery: 697 g (1.54 lbs.)
Including MSR: 712 g (1.57 lbs.)
Paper : 242g (0.53 lbs.)

Battery
7.4 V Li-ion, 2,600 mAh, Rechargeable
Charging time: Up to 4.0 hrs

Performance Characteristics

Memory
64 Mbit SDRAM, 32 Mbit FlashROM

Interface
USB V1.1 FS

Serial
Bluetooth V3.0+EDR
WLAN 802.11 b/g - WEP40/104, WPA1/2
(PSK, EAP)

Environment Characteristics

Temperature
Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity
Operating: 10~80% RH

Sealing
IP54 (with protective case)

Drop Spec
1.5 m (5ft.)

Software

Emulation
BXL / POS

Driver
Windows Driver, OPOS Driver, JPOS Driver,
Linux CUPS Driver

SDK
iOS SDK, Android SDK, Windows SDK,
Symbian SDK

Fonts/Graphics/Symbologies

Character Size
Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN: 24 x 24

Characters Per Line
Font A: 69 Font B, C: 92,
KOR, CHN: 34

Character Sets
Alphanumeric: 95
Expanded Graphics: 128 x 33 page
International: 32

Graphics
Supporting user-defined fonts, graphics, formats,
layouts, and logos

Barcode Symbologies
1D: Codabar, Code 39, Code 93, Code 128, EAN-8,
EAN-13, ITF, UPC-A, UPC-E
2D: Data Matrix, MaxiCode, PDF417, QR code

Accessories

Standard
Belt Strap, Battery Pack, Battery Charger,
Power Cord, Paper

Optional
Shoulder Strap, Single Battery Cradle,
Quad Battery Charger, Vehicle Charger,
Serial/USB Cable, Cleaning Pen

Integrated Card Reader (optional)


MSR
3 Track, DUKPT (optional), T-DES Certified (op-
tional)

Chunicisha, Japan (2014),
Whole Picture of the Printer Market



Global No.1 Spot
in the Mobile Printer Market

Made for
iPod iPhone iPad



BR-SRP-R400-EN-APR15-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co., Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.bixolon.com

